

HiPak Gen4

THORN

96652604 HIPAK GEN4 M LED25000-840 RK BC

UK CA	IP65	▽	IK08	⊕	⚡	⚙️	⚙️	850°C	T _a -20 +45
----------	------	---	------	---	---	----	----	-------	---------------------------

HiPak Gen4


An IP65 single point suspension LED high bay luminaire with rack beam optic. Electronic, DALI-2 dimmable, for 220-240V, 50/60Hz supply. Class I electrical. IK08. Housing: aluminium. Lens/Diffuser: polycarbonate. Supplied without mounting hook, stirrup or rod has to be ordered separately (rigid mounting is recommended). Equipped with 5 pole Quick Connect socket. Wireless controlled via App with Bluetooth® 4.x - basicDIM Wireless Complete with 4000K LED.

ambient temperature: -20°C to +45°C

Dimensions: Ø320 x 170 mm
Luminaire input power: 146.7 W
Luminaire luminous flux: 25000 lm
Luminaire efficacy: 170 lm/W
Weight: 4.15 kg



TLG_HIP4_F_BC_3.jpg



TLG_HIP4_M_ALL.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.