


Chalice 3

THORN

93900897 CHAL3 100 1400-830 HFIX E3 RSB




Chalice 3

A high efficient and sustainable LED downlight with low height. Suitable for mounting in ceiling thicknesses of 1 to 40 mm and Ø100mm cut-out with spring clips. Remote, pluggable, DALI-2 dimmable LED driver NFC configurable, SwitchDIM compatible with 3 hour, manual test, emergency lighting circuit. Body: die-cast aluminium for high efficient thermal management with recycling content >90%. Diffuser: polycarbonate. Reflector and trim: polycarbonate smooth reflector in satinbrite finish with wide beam. Class II electrical, IP54_IP20. Complete with 3000K LED

Dimensions: Ø119 x 75 mm
 Luminaire input power: 16.5 W
 Luminaire luminous flux: 1470 lm
 Luminaire efficacy: 89 lm/W
 Weight: 0.86 kg



TLG_CHAL3_F_100_RSB_EM.jpg



TLG_CHAL3_M_EHF100L.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
 © Thorn Lighting

Chalice 3

93900897 CHAL3 100 1400-830 HFIX E3 RSB

THORN