

ForceLED


A robust dust, dirt and moisture and shock-proof luminaire with IP66 and IK10.


- Design: A compact and lightweight fully recycable aluminium body with a UV stabilised polycarbonate diffuser with linear prisms.
- Efficiency: High efficiency up to 150 lm/W for 3 different lumen outputs 4000, 7000 and 10,000 lm.
- Light distribution: a wide beam distribution with 8% indirect light and UGR<25 for 4000 lm
- Installation: Flexible mounting options with BESA, suspended mounting and outdoor wall mounting (see mounting instructions for details).
- ADDITIONAL OPTIONS: Dimmable (HFI), Emergency (E3, E3D), BasicDIM Wireless (BC), Sensors (MWBC, MWS), Corridor Function (COR,...), Quick Connector & Through Wiring (TW,QC3, QC5,...). See myProduct for all options.



Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.







96636368

Material/Finish

Canopy: fully recyclable die cast aluminium painted white RAL 9010

Diffuser: UV stabilised polycarbonate with linear prisms

Gasket: silicone sponge Fastening clips: stainless steel Quick fix brackets: stainless steel

Installation/Mounting

For surface, suspended and BESA mounting. Quick-fix installation brackets are supplied with each luminaire for surface mounting and optional suspension kit is available (Chain 96502605 & Hook 96631103).



ForceLED

Ordering Guide

| Description | ILCOS Code | Socket | Wt (kg) | SAP Code |
|--------------------------|------------|--------|---------|----------|
| ForceLED | | | | |
| FORCELED 7000-840 HF | LED | | 3 | 96636369 |
| FORCELED 4000-840 HF | LED | | 3 | 96636368 |
| FORCELED 10000-840 HF | LED | | 3 | 96636370 |
| FORCELED 4000 840 HF TW | LED | | 3,3 | 92984177 |
| FORCELED 4000 840 MWS | LED | | 3,1 | 92984181 |
| ForceLED dimmable | | | | |
| FORCELED 4000 840 HFI | LED | | 3 | 92982794 |
| FORCELED 10000 840 HFI | LED | | 3 | 92983480 |
| FORCELED 4000 840 HFI TW | LED | | 3,3 | 92984180 |
| FORCELED 4000 840 BC | LED | | 3,1 | 92984182 |
| FORCELED 4000 840 CORM | LED | | 3,1 | 92984184 |
| FORCELED 7000 840 HFI | LED | | 3 | 92984188 |
| FORCELED 7000 840 BC | LED | | 3,1 | 92984191 |
| FORCELED 7000 840 CORMBC | LED | | 3,1 | 92984192 |
| FORCELED 10000 840 BC | LED | | 3,1 | 92984461 |
| FORCELED 7000-840 MWBC | LED | | 3,1 | 92987925 |