

Sirio Spot

Architecturally pleasing luminaire mixes modern minimalistic design and functionality

- Intelligent characteristics in key areas such as optics, control and flexibility packed into every luminaire
- Optics: The innovative zoom functions allows the Sirio spot to be adjusted from a spot distribution to a wide flood distribution by simply rotating the front bezel. The front bezel is numerically labelled to ensure accuracy and consistency
- Controls: On-boarding dimming function that is perfect for refurbishments or mixing of outputs, without the need of additional control systems. On on-board adjustment switch allows to dim to 10%. Sirio Spot will plug directly into most universal tracks.
- Flexibility: The Sirio spot allows creativity and flexibility with its vario colour temperature feature, by simply adjusting the on-board switch the Sirio can project light in 3000K, 4000K and 5500K with a colour rendering of >90.



Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.

Material/Finish

Optical Lens and track adaptor: polycarbonate

Body: High grade aluminium designed body and heatsink

Installation/Mounting

Suitable for use with Universal 3 circuit recessed, suspended or surface mounted track. Compatible with surface or recessed point outlet.

Ordering Guide

Description	ILCOS Code	Socket	Wt (kg)	SAP Code
Sirio Spot				
SIRIO SPOT LED2000-930-55 STD DIM ZM WH	LED		1	96651968
SIRIO SPOT LED2000-930-55 STD DIM ZM BK	LED		1	96651969
SIRIO SPOT LED2000-930-55 MT3 DIM ZM BK	LED		1	96651967
SIRIO SPOT LED2000-930-55 MT3 DIM ZM WH	LED		1	96651966